AFRL-SR-AR-TR-04-

6638

REPOR	T DOCI	IMENT	ATION	PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect to this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently

1. REPORT DATE (DD-MM-YYYY)	2. REPORT TYPE	3. DATES COVERED (From - To)
09/01/03	Progress	09/01/02-08/31/03
4. TITLE AND SUBTITLE		5a. CONTRACT NUMBER
Fatigue Fracture Analysi	s and Development of Fundamentals of	5b. GRANT NUMBER
Predictive NDE of Adhesi	ve Composite Joints	F49620-01-1-0124
		5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S) Y. A. Dzenis		5d. PROJECT NUMBER
		5e. TASK NUMBER
4		5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAM	8. PERFORMING ORGANIZATION REPORT NUMBER	
University of Nebraska-		
Lincoln, Research Grants		
Contracts Office, Lincoln	n, NE	
68588-0430	Ψ	
9. SPONSORING / MONITORING AGEN	CY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
Air Force Office for	AFOSR	
Scientific Research		
4015 Wilson Boulevard		11. SPONSOR/MONITOR'S REPORT
Arlington, VA 22203-1954		NUMBER(S)
12. DISTRIBUTION / AVAILABILITY STA	ATEMENT	

.

13. SUPPLEMENTARY NOTES

Approved for public release; distribution unlimited

20050104 033

14. ABSTRACT

The objectives of this project are to study durability and damage and fracture development in adhesive composite joints for aerospace structural applications and to develop methods of their intelligent nondestructive evaluations and life prediction. In the third reporting period, the focus was on the development of robust methods of quantitative nondestructive evaluation of crack length and loading mode mixity needed for life prediction in conjunction with the previously developed models of fatigue fracture in joints. Methods of vibrational spectroscopy, acousto-ultrasonics, and acoustic emission location analysis were evaluated experimentally. Dynamic models of wave propagation were developed and used for improved data reduction. A new method of through-thickness interrogation was developed and studied. Specimens with embedded sensors were manufactured and tested. Work has continued on the evaluation of the new composite provided by AFRL. New analytic models were developed for advanced fracture analysis of advanced laminated composites and joints.

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED	ம	8	19b. TELEPHONE NUMBER (include area code)

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39.18

AFOSR Grant No. F49620-01-1-0124

Progress Report 09/01/2002 - 08/31/2003

Grant Data

AFOSR Grant No. F49620-01-1-0124

"Fatigue Fracture Analysis and Development of Fundamentals of Predictive NDE of Adhesive Composite Joints"

Principal Investigator: Yuris Dzenis, Department of Engineering Mechanics, University of Nebraska-Lincoln

Objectives

The main objectives of this project are to study durability and damage and fracture development in adhesive composite joints for aerospace structural applications and to develop methods of their intelligent nondestructive evaluations and life prediction.

Status of Effort

In the third reporting period, the focus was on the development of robust methods of quantitative nondestructive evaluation of crack length and loading mode mixity needed for life prediction in conjunction with the previously developed models of fatigue fracture in joints. Methods of vibrational spectroscopy, acousto-ultrasonics, and acoustic emission location analysis were evaluated experimentally. Dynamic models of wave propagation were developed and used for improved data reduction. A new method of throughthickness interrogation was developed and studied. Specimens with embedded sensors were manufactured and tested. Work has continued on the evaluation of the new composite provided by AFRL. New analytic models were developed for advanced fracture analysis of advanced laminated composites and joints.

Accomplishments / New Findings

Several methods of quantitative nondestructive evaluation of crack tip location in adhesive composite joints were explored. Experimental analysis of vibrational spectroscopy, acousto-ultrasonics (AU), and acoustic emission (AE) methods showed that models were needed for robust quantitative data reduction. Such dynamic models of vibration and wave propagation were developed and used to analyze the experimental data. The vibrational spectroscopy method showed poor resolution for the systems studied. The AE method was found adequate with the disadvantage of being a passive method. The AU method was found to be the best for active interrogation, however the resolution of the conventional longitudinal method of crack detection was poor. Extensive numerical studies were conducted to find optimal sensor-transducer configuration. Multiple sensors and transducers located in different places on and within a joint were modeled. As a result, a new method of through-thickness interrogation was developed. The method was found promising for robust active crack location evaluation. Data reduction methods for the best resolution are currently being investigated. The method can be applied with both external and built-in sensors and transducers.

Specimens with embedded film sensors were manufactured and tested. It was shown that low profile surface mounted and embedded PVDF film sensors can be used for crack detection and AE analysis. PVDF film sensors were able to survive the composite manufacturing temperatures and were sensitive enough to detect dynamic AE signals with broad frequency content. The latter is critically important for the applicability of these sensors for use with our previously developed hybrid transient-parametric method of analysis of fracture and damage micromechanisms in composites and joints. Such analysis with PVDF film sensors is now in progress.

Development of non-destructive methods of evaluation of loading mode mixity continued. AE pattern recognition method discovered previously in our experiments was critically tested based on pioneering statistical numerical modeling of AE signals. Random AE signals from the crack extension events under various types of loads were simulated for the first time using variations of dynamic FEM models developed before. The simulated signals were subjected to pattern recognition analysis and the results were compared with experimental data. It was shown, for the first time that numerical simulation data could be recognized by the pattern recognition system and classified, similar to the experimental AE signals. These results substantially improved the confidence and quality of our previously formulated new nondestructive method of evaluation of the load mixity at the crack tip under. The latter is crucial for the new mechanism-based life prediction of joints.

Work has continued on evaluation of new composite of interest to the Air Force (provided by AFRL – Dr. G. Schoeppner). The new method of experimental evaluation of transverse fracture toughness of advanced composites developed in collaboration with Dr. N. Pagano of AFRL was successfully applied to evaluate an advanced carbon-epoxy

composite. The highest fracture anisotropy for a structural material was measured and reported for the first time. The results can be used in analysis of crack kinking into the composite adherends during fracture of adhesive composite joints.

Finally, several new closed-form SIF solutions for laminates were derived based on fracture mechanics. These solutions enhance the available library of elementary solutions suitable for delaminated composite analysis. Stress singularity indices at free-edges and interfacial crack tips in advanced laminated composites were obtained by means of Stroh's formalism and a general solution procedure was developed for interfacial cracks in multi-layered anisotropic laminates. These results can be used to analyze and further improve the delamination resistance of the novel advanced composites and joints.

Personnel Supported

Principal Investigator:

Y. Dzenis

Graduate Students:

- M. Qin (Ph.D., in progress, will graduate in December of 2003)
- X. Wu (Ph.D., graduated in August, 2003)
- Y. Chen (Ph.D., in progress)
- K. Nistala (M.S., in progress)

Publications and Other Outcomes

Books Edited

"Progress in Non-Destructive Evaluation", Y. Dzenis and C. Cetinkaya, Eds., Proceedings of the NDE Symposium, 2003 ASME International Engineering Congress and Exposition (IMECE2003), American Society of Mechanical Engineering, 2003

Papers

- Dzenis, Y.A., "Cycle-based Analysis of Damage and Failure in Advanced Composites Under Fatigue. 1 Experimental Observation of Damage Development Within Loading Cycles", International Journal of Fatigue, 2003, Vol. 25, No. 6, pp. 499-510
- Dzenis, Y.A., "Cycle-based Analysis of Damage and Failure in Advanced Composites Under Fatigue. 2 Stochastic Mesomechanics Modeling", International Journal of Fatigue, 2003, Vol. 25, No. 6, pp. 511-520
- Dzenis, Y., Qin, M., and Pagano, N., "A Method of Evaluation of Transverse Critical Energy Release Rate (Fiber Failure Mode) in Advanced Composites", International Journal of Fracture, 2003, Vol. 118, No. 1, pp. 11-16
- Wu, X.-F., Dzenis, Y., and Zou, W.-S., "Moving screw dislocation in piezoelectric bimaterials", Physica Status Solidi B: Basic Research, 2003, Vol. 238, No. 1, pp. 120-126
- Wu, X.-F., Dzenis, Y., and Zou, W.-S., "Interfacial Edge Crack between two Bonded Dissimilar Orthotropic Strips under Antiplane Point Loading", ZAMM, 2003, Vol. 83, No. 6, pp. 419-422
- Wu, X.-F., Cohn, S., Dzenis, Y., "Screw Dislocation Interacting with Interface and Interfacial Cracks in Piezoelectric Bimaterials", International Journal of Engineering Science, 2003, Vol. 41, No. 7, pp. 667-682
- Qin, M. and Dzenis, Y.A., "Analysis of Single Lap Adhesive Composite Joints with Delaminated Adherends", Composites B: Engineering, 2003, Vol. 34, No. 2, pp. 167-173
- Wu, X.-F., Dzenis, Y., and Fan, T.-Y., "Two Semi-Infinite Interfacial Cracks Between Two Bonded Dissimilar Elastic Strips", International Journal of Engineering Science, 2003, Vol. 41, No. 15, pp. 1699-1710
- Wu, X.-F., Dzenis, Y., and Fan, T.-Y., "Screw dislocation interacting with twin interfacial edge cracks between two bonded dissimilar piezoelectric strips", Mechanics Research Communications, 2003, 30: 547-555
- Dzenis, Y.A. and Qian, J., "Analysis and Identification of Acoustic Emission from Damage and Internal Friction in Advanced Composites Under Fatigue", Journal of Acoustic Emission, 2002, Vol. 20, pp. 99-107

Dzenis, Y. and Saunders, I., "On the Possibility of Discrimination of Mixed Mode Fatigue Fracture Mechanisms in Adhesive Composite Joints by Advanced Acoustic Emission Analysis", International Journal of Fracture, 2002, Vol. 117, No. 4, pp. 123-128

Wu, X.-F., Dzenis, Y., and Zou, W.-S., "Screw Dislocation Interacting With an Interfacial Edge Crack Between Two Bonded Dissimilar Piezoelectric Wedges", International Journal of Fracture, 2002, Vol. 117, No. 3, pp. 19-114

Qian, J. and Dzenis, Y.A., "Extraction of Histories of Damage Micromechanisms in Unidirectional Composites by Transient-Parametric Analysis", Journal of Acoustic Emission, Dec 2002, Vol. 20, pp. 16-24

Wu, X.-F., Dzenis, Y., "Closed-Form Solution For the Size of Plastic Zone in an Edge-Cracked Strip", International Journal of Engineering Science, 2002, Vol. 40, pp. 1751-1759

Wu, X.-F., Dzenis, Y., "Closed-Form Solution For a Mode-III Interfacial Edge Crack Between Two Bonded Dissimilar Anisotropic Strips", Mechanics Research Communications, 2002, Vol. 29, No. 5, pp. 407-412

Graduated Students

X. Wu, "Fracture of Advanced Laminated Composites", Ph.D. Dissertation, Department of Engineering Mechanics, University of Nebraska-Lincoln, 2003 (Advisor: Y.A. Dzenis)

Interactions/Transitions

Conference Presentations

Dzenis, Y. and Qian, J., "Identification of AE from Internal Fretting in Composites under Fatigue", ASME Paper IMECE2003-43931, 2003 ASME IMECE Procs, 2003, 6 p.

Dzenis, Y., Qin, M., and Pagano, N., "Evaluation of Transverse Critical Energy Release Rate (Fiber Failure Mode) in Advanced Composites", 9th International Conference on The Mechanical Behavior of Materials, Geneva, Switzerland, May 2003

Petersen, B. and Dzenis, Y., "Novel Composites with Nanoparticle Reinforced Interfaces", SES 40th Tech Meeting, Ann Arbor, 2003

Dzenis, Y.A., "Advanced Nanofiber Composites", COMP'03, International Conference on Composite Materials, Corfu, Greece, 2003 (Invited Keynote)

Kwon, O.-Y., Brosig, D., Nistala, K., Dzenis, Y., "A Disposable PVDF Sensor Applied to the Detection of Fatigue Crack Growth in Bonded Composite Joints", ASME Paper IMECE2002-33489, 2002 ASME IMECE Procs (CD-Rom), Vol. 3, 2002, 6 p.

Kwon, O.-Y., Jun, J., Dzenis, Y., "Nondestructive Methods for the Damage Assessment of Cylindrically Curved Composite Laminates Subjected to Low-Velocity Impact", ASME Paper IMECE2002-33430, 2002 ASME IMECE Procs (CD-Rom), Vol. 3, 2002, 6 p.

Dzenis, Y.A., "High-Performance Nanofibers and Nanocomposites", NSF-EC Workshop on Nanomanufacturing and Processing, 2002, San Juan, Puerto Rico (Invited Expert Presentation), 18 p. (Procs. to be published electronically by NSF)

Interactions with AFRL and Private Sector

Dzenis, Y.A., "Fatigue Fracture Analysis and Development of Fundamentals of Predictive NDE of Adhesive Composite Joints", Presentation at AFOSR Mechanics and Materials Program Review, Santa Fe, Sept 2003

Dzenis, Y.A., "Evaluation and Prediction of Fatigue Life of Adhesive Composite Joints", Presentation at AFOSR Mechanics and Materials Program Review, Washington D.C., October 2002

Collaboration with G. Schoeppner and S. Donaldson of AFRL continued. New carbon-epoxy composite prepreg provided by AFRL was successfully tested in adhesive joints by UNL. Feasibility of life prediction by the developed methods was demonstrated on a material of the Air Force interest.

New method of experimental evaluation of transverse fracture toughness of advanced composites developed in collaboration with Dr. N. Pagano of AFRL was successfully applied to evaluate an advanced carbon-epoxy composite. The highest fracture anisotropy for a structural material was measured and reported for the first time. The results can be used in analysis of crack kinking into the composite adherends during fracture of adhesive composite joints.

Honors / Awards

Principal Investigator:

2003	Robert C. McBroom Endowed Professorship
2003	Promoted to Full Professor
2003	UNL College of Engineering Faculty Service Award (one per College)
2003	Faculty Research Award, Department of Engineering Mechanics, UNL
2002	Visiting Professorship, Universite Pierre et Marie Curie - Paris VI, France
2002	Adjunct Associate Professorship, Department of Civil Engineering, Texas A&M University (in conjunction with joint Engineering Study Abroad Program in France)